Email: sales@acculube.com



Product Data

Performance Biolubes NuCut Ultra Lite

Low Viscosity Cutting Oil

Description

Castrol *Performance Biolubes* NuCut Ultra Lite is a light viscosity high performance cutting oil. Formulated with plant-based oils and select additives, it provides lubricity not typically found in conventional mineral-based cutting oils.

Applications

- General purpose cutting and grinding
- Specifically suited for high pressure applications
- Milling, tapping, and reaming
- Gear cutting, broaching, gun drilling and screw machining
- Sharpening high-speed steel and carbide cutting tools

Advantages

- Improves surface finish in machining and grinding operations
- · Superior lubricity maximizes feed rates and improves productivity
- Reduces chip welding so tools maintain a free cutting surface
- Cooler operating and less smoke allow higher operating speeds
- Drastically reduced mist generation
- · Safe for all metals
- Improves centricity, accuracy and part run-out
- Improves part quality by reducing tool or wheel pressure
- Does not contain chlorine
- High flash and fire points

Typical Properties

	Value	Test Method
Appearance	Light Yellow	Visual
Viscosity @40°C, cSt	16.0	CN-TM-101
Viscosity @100°F, SUS	88	CN-TM-101
Flash Point, COC °C (°F)	173 (345)	CN-TM-039
Fire Point, °C (°F)	262 (504)	ASTM D 92
4 Ball Wear, mm	0.45	ASTM D 4172
Pour Point, °C (°F)	-22 (-8)	ASTM D 97
VOC (E1868) – g/L	43	MW-TM-122

Castrol Performance Biolubes NuCut Ultra Lite

17 May 2012

Castrol, Performance Biolubes, NuCut Ultra Lite and the Castrol logo are trademarks of Castrol Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial North America Inc. 150 West Warrenville Road, 603-1E Naperville, IL 60563 Tel: (877) 641 1600 Fax: (877) 648 9801